

# ETA M

EFFECTIVE MAINTENANCE OF HEDGES, DITCHES, AND EMBANKMENTS

Versatile and flexible. Designed for prolonged use with medium sized tractors. Mowing challenging terrain by means of large working range and high degree of movement. Ideal for tractors with limited hydraulic capacity, thanks to potent autonomous hydraulic circuit. Great for the, the specialist landscaper, estates and parks.



## Powerful

Powerful pump with 120 Liter autonomous hydraulic system

## Proven

Reliable and robust Bowden cable operation

## Compact

Collapsible arms for easy transport and storage

## Effective

Double cutting and symmetrical cutting head for 2-sided mowing

## Smooth


Damper on arm for smooth, shock free movement of mower head



## Specifications

Models	Weight kg	Working width mm	Power demand HP	Attachment	PTO RPM	Tool pieces	Rotor diameter mm	Total diameter mm	Min. Tractor weight kg	Reach vertical mm	Reach horizontal mm	Reach depth mm	Hydraulic tank capacity L	Head rotation	Arm max angle	Cutting power mm
M 1100	640	1100	50	CAT II	540	24	108	380	2800	3300	4250	1650	120	168°	128°	40-60

## Spare part



- ☎ +31 6 40 74 20 13
- ✉ sales@aardenburg1974.nl
- 🌐 www.aardenburg1974.nl
- 📍 Valkseweg 46-01, 3771 RE Barneveld, Nederland